



电磁蒸柜
INDUCTION STEAMING CABINET




- 快速升温, 开机5分钟即可出蒸汽;
Fast heating and steam can be produced 5min after start-up;
- 高密封式柜门, 更有效的锁住蒸汽;
Highly-sealed cabinet door capable of locking steam more effectively;
- 内嵌智能保护模组, 可以测量水垢厚度及水位, 最大程度保护水箱, 防止干烧损坏;
Embedded with intelligent protection module that can measure scale thickness and water level and protect water tank to the greatest extent to prevent damage due to dry burning;
- 水电分离, 全自动补水功能;
Water separated from electricity and fully automatic water supplementing function;
- 优质不锈钢外壳, 一体成型台面, IPX5军功级防水设计, 可直冲洗设备;
Excellent stainless-steel housing, integrated bench, IPX5 military-grade waterproof design, and the device can be washed directly;
- 端子接口接线针采用24K黄金涂层, 防止接口在厨房恶劣环境下生锈, 导致接触不良;
24K gold coating adopted for terminal interface wiring pin to prevent the interface from rusting under harsh kitchen environment and resulting in poor contact;
- 可选配自动排污系统, 设备可自动维护。
Automatic blowdown system can be chosen and added to and the device can be maintained automatically.
- 自主研发生产, 从技术源头保证产品质量。
Independent R&D and production to ensure product quality from technical source.




HY-ZG-112




HY-ZG-115



HY-ZG-230



HY-ZG-330



HY-ZGB-330

产品名称 Product name	型号 Model	外形尺寸(mm) Boundary Dimension	电气参数 Electrical parameters
单门蒸饭柜	HY-ZG-112	700*810*1450	380V,50Hz,12kw 6盘(400*600)mm
单门蒸饭柜	HY-ZG-115	700*810*1850	380V,50Hz,15kw 12盘(400*600)mm
双门蒸饭柜	HY-ZG-230	1150*810*1850	380V,50Hz,30kw 24盘(400*600)mm
三门海鲜蒸柜	HY-ZG-330	910*810*1850	380V,50Hz,30kw
三门海鲜蒸柜	HY-ZGB-330	1200*810*1850	380V,50Hz,30kw