

## iCombi Pro overview of models.

### Which model is the right one for you?

The iCombi Pro is available in many different sizes, as ultimately its performance needs to fit your needs and not the other way around. 20 meals or 2,000? Front of house cooking? Size of kitchen? Electricity? Gas? XS? 20-2/1? Which model belongs in your kitchen?

All the options, equipment features and accessories at: [rational-online.com](http://rational-online.com)



**iCombi Classic – technology meets craftsmanship.**  
The iCombi Classic is robust, easy to use and works just as precisely as you. Therefore, it is the tailored solution for those who are experienced and want to operate their combi-steamer manually.



**iVario Pro – Completely different, but still RATIONAL.**  
Boiling, frying, deep-frying the iVario Pro, which works with contact heat, is the ideal addition to the iCombi Pro. Intelligent, convenient, flexible. An unbeatable team.



| iCombi Pro                    | XS 6-2/3              | 6-1/1                      | 10-1/1                     | 6-2/1         | 10-2/1        | 20-1/1                     | 20-2/1        |
|-------------------------------|-----------------------|----------------------------|----------------------------|---------------|---------------|----------------------------|---------------|
| <b>Electric and gas</b>       |                       |                            |                            |               |               |                            |               |
| Capacity                      | 6 × 2/3 GN            | 6 × 1/1 GN                 | 10 × 1/1 GN                | 6 × 2/1 GN    | 10 × 2/1 GN   | 20 × 1/1 GN                | 20 × 2/1 GN   |
| Number of meals per day       | 20–80                 | 30–100                     | 80–150                     | 60–160        | 150–300       | 150–300                    | 300–500       |
| Lengthwise loading (GN)       | 1/2, 2/3, 1/3, 2/8 GN | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 2/1, 1/1 GN   | 2/1, 1/1 GN   | 1/1, 1/2, 2/3, 1/3, 2/8 GN | 2/1, 1/1 GN   |
| Width                         | 655 mm                | 850 mm                     | 850 mm                     | 1072 mm       | 1072 mm       | 877 mm                     | 1082 mm       |
| Depth (including door handle) | 621 mm                | 842 mm                     | 842 mm                     | 1042 mm       | 1042 mm       | 913 mm                     | 1117 mm       |
| Height                        | 567 mm                | 754 mm                     | 1014 mm                    | 754 mm        | 1014 mm       | 1807 mm                    | 1807 mm       |
| Water inlet                   | R 3/4"                | R 3/4"                     | R 3/4"                     | R 3/4"        | R 3/4"        | R 3/4"                     | R 3/4"        |
| Water outlet                  | DN 40                 | DN 50                      | DN 50                      | DN 50         | DN 50         | DN 50                      | DN 50         |
| Water pressure                | 1,0 – 6,0 bar         | 1,0 – 6,0 bar              | 1,0 – 6,0 bar              | 1,0 – 6,0 bar | 1,0 – 6,0 bar | 1,0 – 6,0 bar              | 1,0 – 6,0 bar |
| <b>Electric</b>               |                       |                            |                            |               |               |                            |               |
| Weight                        | 67 kg                 | 99 kg                      | 127 kg                     | 137 kg        | 179 kg        | 263 kg                     | 336 kg        |
| Connected load                | 5,7 kW                | 10,8 kW                    | 18,9 kW                    | 22,4 kW       | 37,4 kW       | 37,2 kW                    | 67,9 kW       |
| Fuse                          | 3 × 10 A              | 3 × 16 A                   | 3 × 32 A                   | 3 × 35 A      | 3 × 63 A      | 3 × 63 A                   | 3 × 100 A     |
| Mains connection              | 3 NAC 400 V           | 3 NAC 400 V                | 3 NAC 400 V                | 3 NAC 400 V   | 3 NAC 400 V   | 3 NAC 400 V                | 3 NAC 400 V   |
| Convection mode output        | 5,4 kW                | 10,25 kW                   | 18 kW                      | 21,6 kW       | 36 kW         | 36 kW                      | 66 kW         |
| Steam mode output             | 5,4 kW                | 9 kW                       | 18 kW                      | 18 kW         | 36 kW         | 36 kW                      | 54 kW         |
| <b>Gas</b>                    |                       |                            |                            |               |               |                            |               |
| Weight                        |                       | 117 kg                     | 155 kg                     | 144 kg        | 192 kg        | 284 kg                     | 379 kg        |
| Electrical rating             |                       | 0,6 kW                     | 0,9 kW                     | 0,9 kW        | 1,5 kW        | 1,3 kW                     | 2,2 kW        |
| Fuse                          |                       | 1 × 16 A                   | 1 × 16 A                   | 1 × 16 A      | 1 × 16 A      | 1 × 16 A                   | 1 × 16 A      |
| Mains connection              |                       | 1 NAC 230 V                | 1 NAC 230 V                | 1 NAC 230 V   | 1 NAC 230 V   | 1 NAC 230 V                | 1 NAC 230 V   |
| Gas connection                |                       | 3/4" IG                    | 3/4" IG                    | 3/4" IG       | 3/4" IG       | 3/4" IG                    | 3/4" IG       |
| <b>Natural gas /LPG*</b>      |                       |                            |                            |               |               |                            |               |
| Max. Nominal thermal load     |                       | 13 kW/13,5 kW              | 22 kW/23 kW                | 28 kW/29,5 kW | 40 kW/42 kW   | 42 kW/44 kW                | 80 kW/84 kW   |
| Convection mode output        |                       | 13 kW/13,5 kW              | 22 kW/23 kW                | 28 kW/29,5 kW | 40 kW/42 kW   | 42 kW/44 kW                | 80 kW/84 kW   |
| Steam mode output             |                       | 12 kW/12,5 kW              | 20 kW/21 kW                | 21 kW/22 kW   | 40 kW/42 kW   | 38 kW/40 kW                | 51 kW/53,5 kW |

\* To guarantee proper operation, the appropriate connection flow pressure must be ensured:

Natural gas H G20 18–25 mbar (0,261–0,363 psi), Natural gas L G25: 20–30 mbar (0,290–0,435 psi), LPG G30 und G31: 25–57,5 mbar (0,363 0,834 psi).

XS and 20-2/1 Electric: ENERGY STAR excludes these unit features from certification.

